

# EASY LIGHT Power LED

5 Years Warranty

Arredamento Interno - indoor

Code/Art. **ATOM 17** **230Vac** ( 17W - lm 2200 ) IP40

Code/Art. **ATOM 31** **230Vac** ( 31W - lm 3900 ) IP40



**PROIETTORE LED** Orientabile 2 assi Attacco a Plafone/Parete  
**LED PROJECTOR** Adjustable both axes 2 phase Ceiling/Wall

Dimensioni  
Dimensions

90 x h125 mm










Beam



# EASY LIGHT Power LED

**PROIETTORE LED** Orientabile 2 assi Attacco a Plafone/Parete  
**LED PROJECTOR** Adjustable both axes 2 phase Ceiling/Wall

Code/Art. <b>ATOM 17 W</b> LED Module 1 x 17	Power Watt : 17	Driver : 230Vac
Code/Art. <b>ATOM 31 W</b> LED Module 1 x 31	Power Watt : 31	Driver : 230Vac
Protection Class : <b>IP44</b>	<b>EN 60529 Class</b>	   <b>RoHS</b>
Ghiera in Alluminio pressofuso : Bianco / Nero <i>Aluminium Ring structure : White / Black</i>		
LED con Struttura dissipante in Alluminio anodizzato <i>LED with Anodized aluminium dissipating structure</i>		
Code/Art. Dimensioni 90 x h125mm <b>ATOM 17 -ATOM 31 Dimensions 90 x h125mm</b>		
LED CRI>80 con protezione trasparente resistente ai raggi UV Lente : <b>40°/25°</b> <i>LED CRI&gt;80 with UV resistant polycarbonate transparent protection Beam : 40°/25°</i>		
Alimentazione 230Vac ON/OFF Direttamente 230Vac - NON dimmerabile <i>Power Supply 230Vac ON/OFF Only No Dimmable</i>		
Possibilità di collegamento elettrico tra più articoli <i>Possibility of electrical connection between more items</i>		
Code / Art.	Kelvin grades / Color Temperature LED	Lumen lm
ATOM 17 -11 40°	 Natural White 4000K	2200
ATOM 17- 12 40°	 Warm White 3000K	2080
ATOM 31 -11 40°	 Natural White 4000K	3900
ATOM 31- 12 40°	 Warm White 3000K	3680

5 Years Warranty - Long Life Power Led