

# EASY LIGHT Power LED


5 Years Warranty

Arredamento Interno - indoor

Code/Art. **VTOR 2** ( 2W - Im 270 ) IP44

**SPOT LED** Tondo LED Orientabile  
**SPOT LED** Round Adjustable LED




**Dimensioni**  
**Dimensions**

 24 x h45 mm

Foro da praticare  
Installation Hole 30mm






## Beam



# EASY LIGHT Power LED

**SPOT LED** Tondo regresso incasso a soffitto

**SPOT LED** Round Downlight recessed

<b>Code/Art. VT0R 2 W</b>		<b>Power Watt : 2</b>	<b>Driver : 500 mA</b>
<b>LED Module 1 x 2</b>			
Protection Class : <b>IP44</b>	<b>EN 60529 Class</b>		  <b>RoHS</b>
Ghiera / Diffusore : Bianco / Cromo <i>Ring / Painted aluminium diffuser : White / Cromo</i>			
LED CRI>80 con protezione trasparente resistente ai raggi UV Lente : 40°/25°/10°/120° <i>LED CRI&gt;80 with UV resistant polycarbonate transparent protection Beam : 40°/25°/10°/120°</i>			
LED con Struttura dissipante in Alluminio anodizzato <i>LED with Anodized aluminium dissipating structure</i>			
Code/Art. <b>VTOR 2</b>	Dimensioni diametro Ø 24 x h45mm <i>Dimensions diameter Ø 24 x h45mm</i>	Foro da praticare diametro Ø: 30mm <i>Installation hole diameter Ø: 30mm</i>	
Alimentazione 230Vac ON/OFF tramite Alimentatore remoto escluso <i>Power Supply 230Vac ON/OFF Remote LED Driver NOT included</i>			
Optional : Alimentatore Dimmer :DALI - 1-10V - PO Pulsante <i>Optional : Dimmable LED Driver :DALI - 1-10V - Open Push</i>			
Possibilità di collegamento elettrico tra più articoli <i>Possibility of electrical connection between more items</i>			
Code / Art.	Kelvin grades / Color Temperature LED	Lumen lm	
VTOR 2 - 10 40°	■ Cold White 5000K	290	
VTOR 2 - 11 40°	■ Natural White 4000K	270	
VTOR 2 - 12 40°	■ Warm White 3000K	240	

5 Years Warranty - Long Life Power Led

[www.ett-led.com](http://www.ett-led.com)

pag.137