



Barra LED versione
LED Bar version

PRO RA

5 Years Warranty
made in Italy

LED High CRI Efficiency Light

Alimentazione **12 / 24 Vdc**
Power Supply

Classe **F III**
Class

Classe di protezione
Class protection

IP40 - Optional IP67



RoHS

Optional



Profilo in alluminio anodizzato
Anodized aluminium profile


Art. CSL 00043

Lunghezza standard
Standard length

1000 mm
39.37 inches

Lunghezza custom
Custom length

da 120 a 3050mm
from 4.7 to 120 inches



Colore profilo disponibile
Available profile color

AA : Anodizzato/Anodized aluminium


AB : Anodizzato nero / Black anodized

AW : Verniciato bianco/ White painted

Diffusore in policarbonato resistente ai raggi UV
UV resistant polycarbonate diffuser

T : Trasparente/Transparent

O : Opalino/Opal





Barra LED versione
LED Bar version

PRO RA

5 Years Warranty
made in Italy

LED High CRI Efficiency Light

Codice Articolo Code	Color / Diffuser Alu / Type	Temperatura di colore LED Color LED Temperature	Power Vdc W/m	Q.ty LED/m	Efficiency Lumen/m
PRO RA 7-10	/ AA / O	■ Cold White 5000K	12/24 7	60	440
PRO RA 7-11	/ AA / O	■ Natural White 4000K	12/24 7	60	410
PRO RA 7-12	/ AA / O	■ Warm White 3000K	12/24 7	60	390
PRO RA 7-12e	/ AA / O	■ Extra Warm 2700K	12/24 7	60	380
PRO RA 7-RGB	/ AA / O	■ ■ ■ R G B	12/24 7	60	320
PRO RA 10-10	/ AA / O	■ Cold White 5000K	12/24 10	120	870
PRO RA 10-11	/ AA / O	■ Natural White 4000K	12/24 10	120	810
PRO RA 10-12	/ AA / O	■ Warm White 3000K	12/24 10	120	790
PRO RA 10-12e	/ AA / O	■ Extra Warm 2700K	12/24 10	120	690
PRORA18 Dual white	/ AA / O	■ ■ Cold/Warm 6/3000K	24 18	120	1200
PRO RA 14-10	/ AA / O	■ Cold White 5000K	24 14	180	1360
PRO RA 14-11	/ AA / O	■ Natural White 4000K	24 14	180	1310
PRO RA 14-12	/ AA / O	■ Warm White 3000K	24 14	180	1260
PRO RA 20-10	/ AA / O	■ Cold White 5000K	24 20	240	1560
PRO RA 20-11	/ AA / O	■ Natural White 4000K	24 20	240	1490
PRO RA 20-12	/ AA / O	■ Warm White 3000K	24 20	240	1460
PRO RA 20-12e	/ AA / O	■ Extra Warm 2700K	24 20	240	1410

Alimentatore LED, Centralina RGB / DMX e Telecomando sono ESCLUSI
LED Driver, RGB / DMX module and Remote control are excluded

Long Life Power LED

www.ett-led.com

pag. 93