



Barra LED versione
LED Bar version

PRO Rca

5 Years Warranty
made in Italy

LED High CRI Efficiency Light

Alimentazione **12 / 24 Vdc** Classe **F III**
Power Supply Class


Classe di protezione **IP40** - Optional **IP67**
Class protection

CE **RoHS** Optional


Profilo in alluminio anodizzato
Anodized aluminium profile

Art. CSL 00089

Lunghezza standard 1000 mm
Standard length 39.37 inches
Lunghezza custom da 120 a 3050mm
Custom length from 4.7 to 120 inches



Steel Fixing clips




Clips di fissaggio
Fixing clips


Colore profilo disponibile **AA** : Anodizzato/Anodized aluminium
Available profile color **AB** : Anodizzato nero / Black anodized
AW : Verniciato bianco/ White painted

Diffusore in policarbonato resistente ai raggi UV
UV resistant polycarbonate diffuser

O : Opalino/Opal



OR : Opalino rotondo/Opal round





Barra LED versione
LED Bar version

PRO Rca

5 Years Warranty
made in Italy

LED High CRI Efficiency Light

Codice Articolo Code	Color / Diffuser Alu / Type	Temperatura di colore LED Color LED Temperature	Power Vdc W/m	Q.ty LED/m	Efficiency Lumen/m
PRO RCa 7-10	/ AA / O	❑ Cold White 5000K	12/24 7	60	440
PRO RCa 7-11	/ AA / O	❑ Natural White 4000K	12/24 7	60	410
PRO RCa 7-12	/ AA / O	❑ Warm White 3000K	12/24 7	60	390
PRO RCa 7-12e	/ AA / O	❑ Extra Warm 2700K	12/24 7	60	380
PRO RCa 7-RGB	/ AA / O	❑ ❑ ❑ R G B	12/24 7	60	320
PRO RCa 18-10	/ AA / O	❑ Cold White 5000K	12/24 18	60	1070
PRO RCa 18-11	/ AA / O	❑ Natural White 4000K	12/24 18	60	1000
PRO RCa 18-12	/ AA / O	❑ Warm White 3000K	12/24 18	60	980
PRO RCa 18-12e	/ AA / O	❑ Extra Warm 2700K	12/24 18	60	960
PRO RCa 18-RGB	/ AA / O	❑ ❑ ❑ R G B	12/24 18	60	890
PRORCa18 Dual white	/ AA / O	❑ ❑ Cold/Warm 6/3000K	24 18	120	1200
PRO RCa 23-10	/ AA / O	❑ Cold White 5000K	12/24 23	75	2020
PRO RCa 23-11	/ AA / O	❑ Natural White 4000K	12/24 23	75	1930
PRO RCa 23-12	/ AA / O	❑ Warm White 3000K	12/24 23	75	1890
PRO RCa 10-10	/ AA / O	❑ Cold White 5000K	12/24 10	120	870
PRO RCa 10-11	/ AA / O	❑ Natural White 4000K	12/24 10	120	810
PRO RCa 10-12	/ AA / O	❑ Warm White 3000K	12/24 10	120	790
PRO RCa 10-12e	/ AA / O	❑ Extra Warm 2700K	12/24 10	120	690
PRO RCa 14-10	/ AA / O	❑ Cold White 5000K	24 14	180	1360
PRO RCa 14-11	/ AA / O	❑ Natural White 4000K	24 14	180	1310
PRO RCa 14-12	/ AA / O	❑ Warm White 3000K	24 14	180	1260
PRO RCa 20-10	/ AA / O	❑ Cold White 5000K	24 20	240	1760
PRO RCa 20-11	/ AA / O	❑ Natural White 4000K	24 20	240	1690
PRO RCa 20-12	/ AA / O	❑ Warm White 3000K	24 20	240	1560
PRO RCa 20-12e	/ AA / O	❑ Extra Warm 2700K	24 20	240	1510
PRO RCa 20-12d	/ AA / O	❑ Extra Warm 2400K	24 20	240	1490
PRO RCa 20-12b	/ AA / O	❑ Extra Warm 2200K	24 20	240	1410

Long Life Power LED
www.ett-led.com