



Barra LED versione
LED Bar version

PRO T Tube

5 Years Warranty
made in Italy

LED High CRI Efficiency Light

Alimentazione **12 / 24 Vdc**
Power Supply

Classe **F III**
Class

Classe di protezione **IP67**
Class protection



Optional



Profilo in alluminio anodizzato
Anodized aluminium profile


Art. CSL 00001

Lunghezza standard **1000 mm**
Standard length

39.37 inches

Lunghezza custom **da 120 a 3050mm**
Custom length

from 4.7 to 120 inches



Clips di fissaggio
Steel spring clips

Colore profilo disponibile
Available profile color

- AA** : Anodizzato/Anodized aluminium
- AB** : Anodizzato nero / Black anodized
- AW** : Verniciato bianco/ White painted

Diffusore in policarbonato resistente ai raggi UV
UV resistant polycarbonate diffuser

T : Trasparente/Transparent



O : Opalino/Opal



L : Lente 10°/10° Lens



OR : Opalino rotondo/Opal round





Barra LED versione
LED Bar version

PRO T Tube

5 Years Warranty
made in Italy

LED High CRI Efficiency Light

Codice Articolo Code	Color / Diffuser Alu / Type	Temperatura di colore LED Color LED Temperature	Power Vdc W/m	Q.ty LED/m	Efficiency Lumen/m
PRO Tube 7-10	/ AA / O	❑ Cold White 5000K	12/24 7	60	440
PRO Tube 7-11	/ AA / O	❑ Natural White 4000K	12/24 7	60	410
PRO Tube 7-12	/ AA / O	❑ Warm White 3000K	12/24 7	60	390
PRO Tube 7-12e	/ AA / O	❑ Extra Warm 2700K	12/24 7	60	380
PRO Tube 7-RGB	/ AA / O	❑ ❑ ❑ R G B	12/24 7	60	320
PRO Tube 18-10	/ AA / O	❑ Cold White 5000K	12/24 18	60	1070
PRO Tube 18-11	/ AA / O	❑ Natural White 4000K	12/24 18	60	1000
PRO Tube 18-12	/ AA / O	❑ Warm White 3000K	12/24 18	60	980
PRO Tube 18-12e	/ AA / O	❑ Extra Warm 2700K	12/24 18	60	960
PRO Tube 18-RGB	/ AA / O	❑ ❑ ❑ R G B	12/24 18	60	890
PRO Tube Dual white	/ AA / O	❑ ❑ Cold/Warm 6/3000K	24 18	120	1200
PRO Tube 23-10	/ AA / O	❑ Cold White 5000K	12/24 23	75	2020
PRO Tube 23-11	/ AA / O	❑ Natural White 4000K	12/24 23	75	1930
PRO Tube 23-12	/ AA / O	❑ Warm White 3000K	12/24 23	75	1890
PRO Tube 10-10	/ AA / O	❑ Cold White 5000K	12/24 10	120	870
PRO Tube 10-11	/ AA / O	❑ Natural White 4000K	12/24 10	120	810
PRO Tube 10-12	/ AA / O	❑ Warm White 3000K	12/24 10	120	790
PRO Tube 10-12e	/ AA / O	❑ Extra Warm 2700K	12/24 10	120	690
PRO Tube 14-10	/ AA / O	❑ Cold White 5000K	24 14	180	1360
PRO Tube 14-11	/ AA / O	❑ Natural White 4000K	24 14	180	1310
PRO Tube 14-12	/ AA / O	❑ Warm White 3000K	24 14	180	1260
PRO Tube 20-10	/ AA / O	❑ Cold White 5000K	24 20	240	1560
PRO Tube 20-11	/ AA / O	❑ Natural White 4000K	24 20	240	1490
PRO Tube 20-12	/ AA / O	❑ Warm White 3000K	24 20	240	1460
PRO Tube 20-12e	/ AA / O	❑ Extra Warm 2700K	24 20	240	1410

Alimentatore LED, Centralina RGB / DMX e Telecomando sono ESCLUSI
LED Driver, RGB / DMX module and Remote control are excluded

Long Life Power LED

www.ett-led.com