



Barra LED versione
LED Bar version

PRO Tt

5 Years Warranty
made in Italy

LED High CRI Efficiency Light

Alimentazione **24 Vdc**
Power Supply

Classe
Class

F III

Classe di protezione
Class protection



RoHS

IP40 - Optional **IP67**

Optional



Profilo in alluminio anodizzato
Anodized aluminium profile


Art. CSL 00060

Lunghezza standard
Standard length

1000 mm
39.37 inches

Lunghezza custom
Custom length

da 120 a 3050mm
from 4.7 to 120 inches



Clips di fissaggio
Steel spring clips


Colore profilo disponibile
Available profile color

AA : Anodizzato/*Anodized aluminium*
AB : Anodizzato nero / *Black anodized*
AW : Verniciato bianco/ *White painted*

Diffusore in policarbonato resistente ai raggi UV
UV resistant polycarbonate diffuser

T : Trasparente/*Transparent*

O : Opalino/*Opal*





Barra LED versione
LED Bar version

PRO Tt

5 Years Warranty
made in Italy

LED High CRI Efficiency Light

Codice Articolo Code	Color / Diffuser Alu / Type	Temperatura di colore LED Color LED Temperature	Power Vdc W/m	Q.ty LED/m	Efficiency Lumen/m
PRO Tt 14-10	/ AA / O	■ Cold White 5000K	24 14	180	1360
PRO Tt 14-11	/ AA / O	■ Natural White 4000K	24 14	180	1310
PRO Tt 14-12	/ AA / O	■ Warm White 3000K	24 14	180	1260
PRO Tt 20-10	/ AA / O	■ Cold White 5000K	24 20	240	1560
PRO Tt 20-11	/ AA / O	■ Natural White 4000K	24 20	240	1490
PRO Tt 20-12	/ AA / O	■ Warm White 3000K	24 20	240	1460
PRO Tt 20-12e	/ AA / O	■ Extra Warm 2700K	24 20	240	1410

Alimentatore LED, Centralina RGB / DMX e Telecomando sono ESCLUSI
LED Driver, RGB / DMX module and Remote control are excluded

Long Life Power LED